INDUSTRIAL BRUSHES · TWISTED STAINLESS WIRE

End brush 25 mm

High-quality twist knot end brush in stainless steel wire for demanding cleaning and surface preparation work.



DIAMETER	SHANK	WIRE	MAX. SPEED
25 mm	6 mm	0.35 mm	20,000 rpm

Suitable for roughening metal surfaces, deburring and cleaning welds – including aluminium welds and hard-to-reach spots. The twisted construction withstands heavy use.

Welds
Aluminium welds
Rust and paint
Deburring

TECHNICAL DATA

Diameter	**25 mm**
Shank	**6 mm**
Overall length	**70 mm**
Filament	**Twisted stainless steel wire**
Wire thickness	**0.35 mm**
Max. speed	**20,000 rpm**

FEATURES

- Very durable twisted construction for heavy use
- Stainless steel wire – good wear resistance
- Efficient removal even in tight spots
- Suitable for metal, steel and other hard surfaces

APPLICATIONS

- Cleaning welds
- Cleaning aluminium welds
- Removing rust and paint
- Roughening surfaces before coating
- Deburring machined parts

⚠ Do not exceed the brush's maximum speed. Wear safety glasses or a face shield and protective gloves.

Request a quote

Tell us what you need and how many – we'll find the right, cost-effective solution for you.

PHONE
+358 45 230 1717

EMAIL
kontel.fi@gmail.com

WEB
www.kontel.fi

Kontel Oy · Pornaistentie 650-22, 04130 Sipoo, Finland